

TULINE WELDING, GRADE R

Red is for acetylene use only, and where cover must resist abrasion, weather and ozone.

Product Number	Nominal I.D.		Nominal O.D.		Reinforcement Spirals	Working Pressure		Min. Bend Radius		Weight	
	(inches)	(mm)	(inches)	(mm)		(psi)	(Mpa)	(inches)	(mm)	(lb/ft)	(Kg/m)
00521403200	3/16	4.76	0.44	11.11	2	200	1.38	1.25	31.75	0.15	0.22
00521404200	1/4	6.35	0.53	13.49	2	200	1.38	1.50	38.10	0.21	0.32
00521405200	5/16	7.94	0.59	15.08	2	200	1.38	2.00	50.80	0.25	0.37
00521406200	3/8	9.53	0.66	16.67	2	200	1.38	2.25	57.15	0.28	0.41

TULINE WELDING, GRADE R – Cut & Coupled (B&B)

Product Number	Nominal I.D.		Lengths	
	(inches)	(mm)	(feet)	(meters)
00521403215▲	3/16	4.76	12.50	3.81
00521403225	3/16	4.76	25.00	7.62
00521403249	3/16	4.76	50.00	15.24
00521403291	3/16	4.76	100.00	30.48
00521484212▲	1/4	6.35	12.50	3.81
00521484225	1/4	6.35	25.00	7.62
00521484250	1/4	6.35	50.00	15.24
00521484290	1/4	6.35	100.00	30.48
00521405226▲	5/16	7.94	25.00	7.62
00521405252	5/16	7.94	50.00	15.24
00521405291▲	5/16	7.94	100.00	30.48
00521406226▲	3/8	9.53	25.00	7.62
00521406251▲	3/8	9.53	50.00	15.24
00521406290▲	3/8	9.53	100.00	30.48



▲ = Make To Order (MTO)

SINGLE LINE CORRUGATED WELDING, GRADE R, TYPE S

Red or Green. Red is for acetylene use only, and where cover must resist abrasion, weather and ozone.

Product Number	Nominal I.D.		Nominal O.D.		Reinforcement Spirals	Working Pressure		Min. Bend Radius		Weight	
	(inches)	(mm)	(inches)	(mm)		(psi)	(Mpa)	(inches)	(mm)	(lb/ft)	(Kg/m)
Green											
00521803205	3/16	4.76	0.44	11.11	2	200	1.38	1.25	31.75	0.08	0.12
00521804205	1/4	6.35	0.53	13.49	2	200	1.38	1.50	38.10	0.11	0.16
00521804405	1/4	6.35	0.59	15.08	4	200	1.38	1.50	38.10	0.14	0.21
00521805400▲	5/16	7.94	0.66	16.69	2	200	1.38	2.00	50.80	0.16	0.24
00521806400	3/8	9.53	0.72	18.26	2	200	1.38	2.25	57.15	0.18	0.27
Red											
00521903205	3/16	4.76	0.44	11.11	2	200	1.38	1.25	31.75	0.08	0.12
00521904205	1/4	6.35	0.53	13.49	2	200	1.38	1.50	38.10	0.11	0.16
00521904405	1/4	6.35	0.59	15.08	4	200	1.38	1.50	38.10	0.14	0.21
00521905400	5/16	7.94	0.66	16.69	2	200	1.38	2.00	50.80	0.16	0.24
00521906400	3/8	9.53	0.72	18.26	2	200	1.38	2.25	57.15	0.18	0.27

▲ = Make To Order (MTO)