

## TRANSPORTER® RED TANK TRUCK

The Transporter Red Tank Truck hose is recommended for use to handle the bulk transfer of petroleum products. This hose will also handle most hydrocarbons with aromatic content up to 55% maximum, fats, greases, animal oil, vegetable oil, hydraulic fluid and a wide range of chemicals. The NBR tube gives excellent resistance to oil, while the NBR/PVC cover is both oil and weather resistant. Transporter Red Tank Truck hose is rated at **full vacuum**.



<b>Resistance:</b>
<b>Branding:</b>
Thermoid HBD Industries Inc. Transporter Tank Truck Made In USA

- Cover Color:** Red
- Oil Resistance:** High
- Construction:**
  - Tube:** NBR, RMA Class A
  - Cover:** NBR/PVC, RMA Class B
  - Reinforcement:** Spiral steel wire helix(es) between synthetic textile plies
- Temperature Range:** -30°F to +200°F  
-34°C to +93°C
- Packaging:** 100 ft. maximum

Product Number	Nominal I.D.		Nominal O.D.		Plies	Working Pressure		Min. Bend Radius		Weight	
	(inches)	(mm)	(inches)	(mm)		(psi)	(Mpa)	(inches)	(mm)	(lb/ft)	(Kg/m)
17813015002	1-1/2	38.10	2.00	50.80	2	150	1.03	4.50	114.30	0.80	1.19
17813020002	2	50.80	2.47	62.71	2	150	1.03	6.00	152.40	1.00	1.49
17813025002▲	2-1/2	63.50	3.06	77.79	2	150	1.03	7.50	190.50	1.50	2.23
17813030002	3	76.20	3.56	90.49	2	150	1.03	9.00	228.60	1.70	2.53
17813040002	4	101.60	4.63	117.48	2	150	1.03	12.00	304.80	2.50	3.72

▲ = Make To Order (MTO)

## TRANSPORTER® BLACK TANK TRUCK

The Transporter Black Tank Truck hose is rated at **full vacuum**. Like the red version, this hose is recommended for most hydrocarbons with aromatic content up to 55% maximum, fats, greases, animal oil, vegetable oil, hydraulic fluid and a wide range of chemicals. The black NBR tube has high oil resistance. The NBR/PVC cover is both oil and abrasion resistant.



<b>Resistance:</b>
<b>Branding:</b>
Thermoid HBD Industries Inc. Transporter Tank Truck Made In USA

- Cover Color:** Black
- Oil Resistance:** High
- Construction:**
  - Tube:** NBR, RMA Class A
  - Cover:** NBR/PVC, RMA Class B
  - Reinforcement:** Spiral steel wire helix(es) between synthetic textile plies
- Temperature Range:** -30°F to +200°F  
-34°C to +93°C
- Packaging:** 1"-4" I.D. – 100 ft. maximum  
6" I.D. – 50 ft.; 100 ft. available upon request

Product Number	Nominal I.D.		Nominal O.D.		Plies	Working Pressure		Min. Bend Radius		Weight	
	(inches)	(mm)	(inches)	(mm)		(psi)	(Mpa)	(inches)	(mm)	(lb/ft)	(Kg/m)
17811008002	1	25.40	1.50	38.10	2	200	1.38	2.50	63.50	0.50	0.74
17811010002	1-1/4	31.75	1.75	44.45	2	200	1.38	3.00	76.20	0.70	1.04
17811015002	1-1/2	38.10	2.00	50.80	2	150	1.03	4.50	114.30	0.80	1.19
17811020002	2	50.80	2.47	62.71	2	150	1.03	6.00	152.40	1.00	1.49
17811025002	2-1/2	63.50	3.06	77.79	2	150	1.03	7.50	190.50	1.50	2.23
17811030002	3	76.20	3.56	90.49	2	150	1.03	9.00	228.60	1.70	2.53
17811040002	4	101.60	4.63	117.48	2	150	1.03	12.00	304.80	2.50	3.72
17811060002▲	6	152.40	6.78	172.24	2	100	0.69	30.00	762.00	5.00	7.44

▲ = Make To Order (MTO)